

AB5303B

Audio Player Microcontroller

Versions: 0.0.1

2018/09/27

Declaration

Copyright © 2018, www.bluetrum.com.

All Rights Reserved. No Unauthorized Distribution.

Bluetrum reserves the right to make changes without further notice to any products herein to improve reliability, function or design.

For further information on the technology, product and business term, please contact Bluetrum Company.

For sales or technical support, please send email to the address:

Sales: sales@bluetrum.com

Technical: project@bluetrum.com

Bluetrum Technology

Revision History

Date	Version	Comments	Revised by
2018-09-27	0.0.1	First draft	Leo

Table of Contents

TABLE OF CONTENTS.....	3
1 PRODUCT FEATURES	4
2 PACKAGE DEFINITION	5
2.1 PIN ASSIGNMENT.....	5
2.2 PIN DESCRIPTIONS	5
3 CHARACTERISTICS.....	9
3.1 PMU PARAMETERS.....	9
3.2 IO PARAMETERS	9
3.3 AUDIO DAC PARAMETERS.....	10
3.4 AUDIO ADC PARAMETERS.....	10
3.5 BT PARAMETERS.....	10
3.6 CURRENT PARAMETERS	11
4 PACKAGE INFORMATION	12

1 Product Features

CPU and Flexible IO

- ⊕ 32bit High performance CPU with DSP instruction;
- ⊕ Flexible GPIO pins with Programmable pull-up and pull-down resistors;
- ⊕ Support GPIO wakeup or interrupt;

Bluetooth Radio

- ⊕ Compliant to Bluetooth 5.0 and BLE specification (QDID: [115952](#));
- ⊕ TX output power +2db in typical;
- ⊕ RX Sensitivity with -90.5dBm @Basic Rate;

FM Tuner

- ⊕ Support frequency band 76~108MHz;
- ⊕ Auto search tuning;
- ⊕ Programable de-emphasis(50/75uS);
- ⊕ Receive signal strength indicator (RSSI);

Audio Interface

- ⊕ Audio codec with 16bit stereo DAC and two channel 16bit ADC;
- ⊕ Support flexible audio EQ adjust;
- ⊕ Support Sample rate 8, 11.025, 12, 16, 22.05, 32, 44.1 and 48KHz;
- ⊕ 4 channel Stereo Analog MUX;
- ⊕ Two channel MIC amplifier input;
- ⊕ High performance Stereo audio ADC with 90dB SNR;

- ⊕ High performance Stereo audio DAC with 95dB SNR, with headphone amplifier output;

Peripheral and Interfaces

- ⊕ Three 32-bit timers;
- ⊕ Three multi-function 32-bit timers, support Capture and PWM mode;
- ⊕ WatchDog;
- ⊕ Three full-duplex UART;
- ⊕ SPI;
- ⊕ IR controller;
- ⊕ SD Card Host controller;
- ⊕ Full speed USB 2.0 HOST/DEVICE controller;
- ⊕ Sixteen Channels 10-bit SARADC;
- ⊕ Build in PMU, such as LDO;

Package

- ⊕ SSOP28L;

Temperature

- ⊕ Operating temperature: -40°C to +85°C;
- ⊕ Storage temperature: -65°C to +150°C ;

2 Package Definition

2.1 Pin Assignment

1	PB0	PB1	28
2	PWRKEY	PB2	27
3	BT_ANT	VDDBT	26
4	BT_OSCI	DGND	25
5	BT_OSCO	VBAT	24
6	PB4/USB_DM	VDDIO	23
7	PB3/USB_DP	PE0	22
8	PA7	PE7	21
9	PA6	FM_ANT	20
10	PA5	AGND	19
11	PA2	VDDDAC	18
12	PA0	DACL	17
13	PF5	DACR	16
14	PF4	MICL/PF2	15

Figure 2-1 Pin assignment for SSOP28L

2.2 Pin Descriptions

Table 2-1 SSOP28Lpin description

Pin No.	Name	Type	Function
1	PB0	I/O	FM/AM-G0 SPDIF2 SDCMD-G2 SPI1DI-G3 FMOSC-G3 PWM0-T3 TMR3CAP_G3/IR_G3 PB0
2	PWRKEY	A	Power key input
3	BT_ANT	A	BT ANT
4	BT_OSCI	A	26M OSC input
5	BT_OSCO	A	26M OSC output
6	PB4/USB_DM	I/O	ADC6 USB DM SPI0CLK-G3

			RX0-G3 PB4
7	PB3/USB_DP	I/O	ADC5 USB DP SPI0DO-G3 TX0-G3 PB3
8	PA7	I/O	ADC2 AUXR0 SDDAT0-G1 SPI1DO-G2 TX0-G1 TX1-G1 HSTRX-G1 PWM2-T4 PA7
9	PA6	I/O	ADC1 AUXL0 SDCLK-G1 SPI1CLK-G2 RX0-G1 RX1-G1 HSTRX-G6 FMOSC-G2 PWM1-T4 TMR3CAP_G2/IR_G2 PA6
10	PA5	I/O	ADC0 SDCMD-G1 SPI1DI-G2 FMOSC-G1 PWM0-T4 TMR3CAP_G1/IR_G1 PA5
11	PA2	I/O	SPI1DI-G1 LPWM2-G3 IISCLK-G1 PA2
12	PA0	I/O	SPDIF0 RX0-G5 HSTRX-G10 LPWM0-G3 IISDI-G1 PA0
13	PF5	I/O	PF5
14	PF4	I/O	PF4

15	MICL/PF2	I/O	ADC10 MICL SPI1DO-G5 TX0-G7 LPWM3-G2 PF2
16	DACR	A	DAC R
17	DACL	A	DAC L
18	VDDDAC	PWR	DAC power
19	AGND	GND	DAC Ground
20	FM_ANT	A	FMRX ANT
21	PE7	I/O	ADC9 AUXR2 SDDAT0-G3 SPI1DO-G4 TX0-G4 HSTRX-G4 LPWM3-G1 TMR4CAP_G1/IR_G8 PE7
22	PE0	I/O	SPI0DI-G3 TX0-G6 LPWM2-G2 IISDI-G2 TMR3CAP_G5/IR_G5 PE0
23	VDDIO	PWR	VDDIO power output
24	VBAT	PWR	VBAT power input
25	DGND	GND	Digital Ground
26	VDBBT	PWR	BT power
27	PB2	I/O	ADC4 AUXR1 SDDAT0-G2 SPI1DO-G3 TX0-G2 TX2-G2 HSTRX-G2 PWM2-T3 PB2
28	PB1	I/O	ADC3 FM/AM-G1 AUXL1 SDCLK-G2 SPI1CLK-G3 RX0-G2 RX2-G2 HSTRX-G7 FMOSC-G4

			PWM1-T3 TMR3CAP_G4/IR_G4 PB1
--	--	--	------------------------------------

Note: I/O: Digital input/output; I : Digital input; A : Analog Pin; PWR: Power Pin; GND: Ground.

3 Characteristics

3.1 PMU Parameters

Table 3-1 PMU voltage input Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
VUSB	Charger Voltage input	3.0	5.0	5.0	V	
VBAT	Voltage input	3.0	3.7	5.0	V	

Table 3-2 3.3V LDO Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
VDDIO	3.3V LDO voltage output	3.0	3.3	3.6	V	Light Loading condition
△VVDDIO	Output Mismatch 1-sigma	-	56	-	mV	VDDIO=3.3v
ILOAD	Maximum output current	-	-	150	mA	@VBAT=3.6v
ISC	Short Circuit Current Limit	-	-	300	mA	@VBAT=3.8v

Table 3-3 1.6V LDO Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
VDDBT	1.6V LDO voltage output	-	1.6	-	V	Light Loading condition
△VVDDBT	Output Mismatch 1-sigma	-	27	-	mV	VDDBT=1.6v
ILOAD	Maximum output current	-	-	100	mA	@VBAT=3.0v
ISC	Short Circuit Current Limit	-	-	200	mA	@VBAT=3.8v

Table 3-4 1.2V LDO Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
VDDCORE	1.2V LDO voltage output	-	1.2	-	V	Light Loading condition
△VVDDCORE	Output Mismatch 1-sigma	-	20	-	mV	VDDCORE=1.2v
ILOAD	Maximum output current	-	-	80	mA	@VBAT=3.6v
ISC	Short Circuit Current Limit	-	-	120	mA	@VBAT=3.8v

3.2 IO Parameters

Table 3-5 I/O Parameters

GPIO—Electrical Characteristics							
Symbol	Description	Related GPIO	Min	Typical	Max	Units	Conditions
V _{IL}	Low-level input voltage		-0.3		1.27	V	VDDIO=3.3V
V _{IH}	High-level input voltage		2.03		3.6	V	VDDIO=3.3V
Driver Ability 1	Output Driver Ability 1			32		mA	VDDIO=3.3V
Driver Ability 0	Output Driver Ability 0			8		mA	VDDIO=3.3V
R _{PUP0}	Internal pull-up resister 0		8	10	12	KΩ	
R _{PUP1}	Internal pull-up resister 1		0.24	0.3	0.36	KΩ	
R _{PUP2}	Internal pull-up resister 2		160	200	240	KΩ	
R _{PDN0}	Internal pull-down resister 0		8	10	12	KΩ	
R _{PDN1}	Internal pull-down resister 1		0.24	0.3	0.36	KΩ	
R _{PDN2}	Internal pull-down resister 2		160	200	240	KΩ	

3.3 Audio DAC Parameters

Table 3-6 Audio DAC Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
SNR		-	96	-	dB	VCM cap=1uF VDDDAC cap=1uF with A-wt filter Output -3dBV Fin=1KHz
THD+N		-	-86	-	dB	VCM cap=1uF VDDDAC cap=1uF with A-wt filter Output -3dBV with 10K loading Fin=1KHz
Output Range	Maximum output voltage	-	2.6		V _{peak-peak}	32ohm Loading

3.4 Audio ADC Parameters

Table 3-7 Audio ADC Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
SNR		-	90	-	dB	VCM cap=1uF VDDDAC cap=1uF with A-wt filter Input sine amplitude, 850mV RMS Fin=1KHz
THD+N		-	-87	-	dB	VCM cap=1uF VDDDAC cap=1uF with A-wt filter Input sine amplitude, 850mV RMS Fin=1KHz.
Input Range	Input sine wave peak amplitude	0		VCM	V	From aux input, aux 0db gain, VCM represent VCM voltage.

3.5 BT Parameters

Table 3-8 BT Parameters

Characteristics	Min	Typical	Max	Unit	Conditions
Maximum Transmit Power	-	2	-	dBm	
RMS DEVM	-	5.5	-	%	
Peak DEVM	-	12.5		%	Maximum TX power 2-DH5 packet
EDR Relative Transmit Power		-0.2		dB	
Sensitivity @ Basic Rate		-90.5		dBm	BER=0.1%, using DH5 packet
Sensitivity @ EDR		-89.5		dBm	BER=0.01%, using 2-DH5 packet

3.6 Current Parameters

Table 3-9 Current Parameters

Sym	Characteristics	Min	Typ	Max	Unit	Conditions
IRTC	RTC mode current	-	4	-	uA	4.2V input, room temp.
Sleep	Sleep current	-	500	2000	uA	3.3V input, room temp

4 Package Information